

tiptel Htek UC903

Zakelijke HD IP telefoon

De tiptel Htek UC903 biedt superieure HD-geluidskwaliteit en is voorzien van de benodigde functies, zoals 2 SIP accounts, actie URL. Alle functies en software evenals de provisionings tabel zijn voor alle modellen gelijk. Het is een perfecte keuze voor kleine en middelgrote bedrijven op zoek naar een kwalitatief hoge functierijke IP-telefoon tegen een betaalbare prijs.

Highlights

tiptel Htek UC903

- 2,7"/7,0 cm grafisch display, achtergrondverlichting, 192 x 64 pixels
- 3 VoIP-accounts
- 6 softkeys
- 10/100 Mbit/s Dual-port Ethernet
- Power over Ethernet (PoE)
- HD-audio en ondersteuning voor gangbare smalband-codecs smalband-codecs



tiptel
Htek

tiptel Htek UC903

Zakelijke HD IP telefoon



Phone Features

- 3 SIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Redial, call return, auto answer, direct IP call
- 5-way conferencing
- Group listening, SMS, emergency call
- Ring tone selection/provisioning
- Set date time automatically or manually
- Dial plan per account
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Action URL/URI

Voice Codecs Features

- HD voice: HD handset, HD speaker
- Codecs: iLBC, G.722, G.711(A/μ), GSM_FR, G.723, G.729AB, G.726-32
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, AGC, CNG, AEC, PLC, AJP

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Busy Lamp Field (BLF), bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI), voice mail
- Intercom, paging
- Call park, call pickup
- Music on hold
- Hot-desking

Display and Indicator

- 192 x 64 pixel graphical LCD with backlight
- LED for call and message waiting indication
- Illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name, number

Feature keys

- 6 line keys with LED
- 6 line keys can be programmed up to
- 20 various features (4-page view)
- 8 features keys: voice mail, headset, mute, speaker, conference, hold, transfer, redial
- 4 context-sensitive "soft" keys
- 6 navigation keys, volume control keys
- Illuminated speaker key/headset key/mute key

Interface

- Dual-port 10/100M Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port

Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External universal AC adapter :
AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.6~4.2W
- Power consumption (PoE): 2.1~5.1W
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Management

- Configuration: browser/LCD-Menu/auto-provision
- Auto provision via HTTP/HTTPS FTP/TFTP
- Auto-provision with PnP
- Reset to factory, restart, reboot
- Local tracing log export, system log
- Phone lock for personal privacy protection

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server/proxy redundancy
- NAT Traversal: STUN mode
- DHCP/static/PPPoE/IEEE802.1X/open VPN
- HTTP/HTTPS web server
- Time and date synchronization by SNTP
- DNS-NAPTR/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- TLS(Transport Layer Security), SRTP
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess

Tiptel Nederland

Camerastraat 2
NL-1322 BC Almere
☎ +31 (0) 36 53 666 50
☎ +31 (0) 36 53 678 81
✉ info@tiptel.nl
🌐 www.tiptel.nl

Tiptel België

Imperiastraat 10/B8
B-1930 Zaventem
☎ +32 (0) 2 7149333
☎ +32 (0) 2 7149334
✉ info@tiptel.be
🌐 www.tiptel.be

