

tiptel Htek UC926E

Zakelijke HD IP telefoon met Bluetooth en WiFi

De tiptel Htek UC926E is een innovatieve Gigabit Color IP Phone met 4,3" TFT-LCD scherm met 480 x 272 pixels. Deze telefoon ondersteunt 5-weg conferentie. Uitbreidbaar met een keymodule UC46 en 16 SIP accounts. De UC926E is voorzien van vele functies en eenvoudig in gebruik. De hoge resolutie TFT-LCD en HD Voice brengen je een levensechte visuele- en geluidservaringen.



Highlights

tiptel Htek UC926E

- 4,3"/480x272 pixel TFT-LCD kleurendisplay met achtergrondverlichting, Wallpapers, 262.000 kleuren
- 16 SIP-accounts
- 10 softkeys
- 10/100/1000 Mbit/s Dual-port Ethernet
- Power over Ethernet (PoE)
- HD-audio en ondersteuning voor gangbare smalband-codexs
- Support Bluetooth & WiFi



tiptel Htek UC926E

Zakelijke HD IP telefoon



Phone Features

- 6 SIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Redial, call return, auto answer, direct IP call,
- 5-way conferencing
- XML Browser, action URL/URI
- Group listening, SMS, emergency call
- Ring tone selection/provisioning
- Set date time automatically or manually
- Dial plan per account
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Voice Codex Features

- HD voice: HD handset, HD speaker
- Codecs: iLBC, G.722, G.711(A/μ), GSM_FR, G.723, G.729AB, G.726-32
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, AGC, CNG, AEC, PLC, AJB

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Busy Lamp Field (BLF), bridged Line Appearance(BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI) , voice mail
- Call park, call pickup
- Intercom, paging
- Music on hold
- Hot-desking

Display and Indicator

- 4.3" 480 x 272 pixel color display with backlight
- 24 bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated
- LEDs for line status information
- Intuitive user interface with icons and soft keys
- Wallpaper, national language selection
- Caller ID with name, number and photo

Feature keys

- 10 line keys with LED
- 10 line keys can be programmed up to
- 36 various features (4-page view)
- 8 features keys: voice mail, headset, mute, speaker, conference, hold, transfer, redial,
- 4 context-sensitive "soft" keys
- 6 navigation keys ,volume control keys
- Illuminated speaker key/headset key/mute key

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 3
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port
- Supports up to 6 Expansion Modules

Physical Features

- Stand with 3 adjustable angles
- Wall mountable
- External universal AC adapter :
■ AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 2.0~4.6W
- Power consumption (PoE): 2.5~5.5W
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Management

- Configuration: browser/LCD-Menu/auto-provision
- Auto provision via HTTP/HTTPS FTP/TFTP
- Auto-provision with PnP
- Reset to factory, restart, reboot
- Local tracing log export, system log
- Phone lock for personal privacy protection

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server/proxy redundancy
- NAT Traversal: STUN mode
- DHCP/static/PPPoE/IEEE802.1X/open VPN
- HTTP/HTTPS web server
- Time and date synchronization by SNTP
- DNS-NAPTR/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- TLS (Transport Layer Security), SRTP
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess

Bluetooth

- Bluetooth V 4.0+HSsystem.
- Enhanced Data Rate (EDR) compliant both 2Mbps and 3Mbps supported.
- Bluetooth frequency range: 2.402GHz-2.480GHz Compatible with Bluetooth specification V4.0,back compatible with Bluetooth 1 .2 2.0 and 3.0 or wide-ranging use.

WiFi

- Network Standard: IEEE802 .11b/g/n.
- Transmission Rate: 1 50 Mbps.
- Frequency Range: 2.4GHz.

**Tiptel
Nederland**

Camerastraat 2

NL-1322 BC Almere

☎ +31 (0) 36 53 666 50

☎ +31 (0) 36 53 678 81

✉ info@tiptel.nl

🌐 www.tiptel.nl

**Tiptel
België**

Imperiastr

aat 10/B8

B-1930

Zaventem

☎ +32 (0) 2 7149333

☎ +32 (0) 2 7149334

✉ info@tiptel.be

🌐 www.tiptel.be

