

tiptel Htek UC903

Das leistungsstarke, preisgünstige IP-Telefon mit beleuchtetem Display

Die Telefone der tiptel Htek UC900-Serie sind reich an Funktionen, ausgesprochen komfortabel und preislich attraktiv. Das monochrome LC-Display des tiptel Htek UC903 erlaubt eine einfache Bedienung. Mit sechs programmierbaren Displaytasten lässt es sich optimal an Ihre Bedürfnisse anpassen. Die Displaytasten sind in 4 Ebenen belegbar, so dass insgesamt ohne jegliche Erweiterungstastenfelder bis zu 20 Funktionstasten z.B. für Besetztlampenfeld-Funktion zur Verfügung stehen. Das Telefon verfügt über Anschlussmöglichkeit für ein schnurgebundenes Headset, die Stromversorgung erfolgt über PoE, alternativ über ein optionales Steckernetzgerät.

Highlights

tiptel Htek UC903

- Grafisches LC-Display, 192 x 64 Punkte, monochrom, hintergrundbeleuchtet
- 3 VoIP-Accounts
- 6 Displaytasten
- Power over Ethernet (PoE)
- Auto-Provisionierung



tiptel

tiptel Htek UC903

Das leistungsstarke, preisgünstige IP-Telefon mit beleuchtetem Display



Phone Features

- 3 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Redial, call return, auto answer, direct IP call
- 5-way conferencing
- Group listening, SMS, emergency call
- Ring tone selection/provisioning
- Set date time automatically or manually
- Dial plan per account
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Action URL/URI

Voice Codecs Features

- HD voice: HD handset, HD speaker
- Codecs: iLBC, G.722, G.711(A/μ), GSM_FR, G.723, G.729AB, G.726-32
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, AGC, CNG, AEC, PLC, AJB

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Busy Lamp Field (BLF), bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI), voice mail
- Intercom, paging
- Call park, call pickup
- Music on hold
- Hot-desking

Display and Indicator

- 192 x 64 pixel graphical LCD with backlight
- LED for call and message waiting indication
- Illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name and number

Feature keys

- 6 line keys with LED
- 6 line keys can be programmed up to
- 20 various features (4-page view)
- 8 features keys: voice mail, headset, mute, speaker, conference, hold, transfer, redial
- 4 context-sensitive "soft" keys
- 6 navigation keys, volume control keys
- Illuminated speaker key/headset key/mute key

Interface

- Dual-port 10/100M Ethernet

- Power over Ethernet (IEEE 802.3af), class 2
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port

Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External universal AC adapter :
AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.6~4.2W
- Power consumption (PoE): 2.1~5.1W
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Management

- Configuration: browser/LCD-Menu/auto-provision
- Auto provision via HTTP/HTTPS FTP/TFTP
- Auto-provision with PnP
- Reset to factory, restart, reboot
- Local tracing log export, system log
- Phone lock for personal privacy protection

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server/proxy redundancy
- NAT Traversal: STUN mode
- DHCP/static/PPPoE/IEEE802.1X/open VPN
- HTTP/HTTPS web server
- Time and date synchronization by SNTP
- DNS-NAPTR/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- TLS(Transport Layer Security), SRTP
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess

Tiptel b.v.

Camerastraat 2
1322 BC Almere
Niederlande
☎ +31 (0) 36 53 666 50
☎ +31 (0) 36 53 678 81
✉ info@tiptel.nl
🌐 www.tiptel.nl

Tiptel NV

Imperiastraat 10/B8
1930 Zaventem
Belgien
☎ +32 (0) 2 7149333
☎ +32 (0) 2 7149334
✉ info@tiptel.be
🌐 www.tiptel.be